

## PRODUCT DATA SHEET

---

Part number 431707

---

EAN 4015609122134

Manufacturer WALTHER-WERKE

WEEE-Reg.-Number: DE 22131895

### Product description

---

Panel socket straight 32A 7P 7h with screwed flange 80x80mm



Similar image

### Detailed product description

---

WALTHER Panel socket 32A 7P 500V 7h IP44  
 straight  
 made from PA6 material  
 finger-safe in accordance with BGV A3  
 with screwed flange  
 flange 80x80  
 fixing center 60x60

### Ordering Information

---

|                         |          |
|-------------------------|----------|
| Order unit              | Piece    |
| Customs number          | 85366990 |
| Net weight              | 0,277 kg |
| Packing quantity (VPE)  | 10       |
| Length of the packaging | 0,31 m   |
| Width of the packaging  | 0,255 m  |
| Depth of the packaging  | 0,15 m   |
| Gross weight(VPE)       | 2,966 kg |

### Classification system

---

|                       |          |
|-----------------------|----------|
| Classification system | ETIM_6.0 |
| ETIM Class            | EC001317 |

## Technical product data

|                                       |                        |
|---------------------------------------|------------------------|
| IEC-ampereage                         | 32 A                   |
| Amperage acc. UL/CSA (for UL-version) | 30 A                   |
| Number of poles                       | 7                      |
| Voltage acc. EN 60309-2               | 500 V (50+60 Hz) black |
| Clock hour position                   | 7 h                    |
| Identification colour                 | Black                  |
| RAL-number                            | 9005                   |
| Degree of protection (IP)             | IP44                   |
| Connection system                     | Screwed terminal       |
| Angle of plug                         | Straight               |
| Material                              | Plastic                |
| Military model                        | False                  |
| Flange size vertical                  | 80 mm                  |
| Drill hole distance vertical          | 60 mm                  |
| Flange size horizontal                | 80 mm                  |
| Drill hole distance horizontal        | 60 mm                  |

## Dimension sheet

